

# **AGRÓNIC 52**



Device which blends in continuously the two waters to obtain a programmed conductivity, by using one or two motorized valves.

It works through three formulas or programs that are started by external orders, gathered up by the corresponding inputs.

You can do the programming either by the conductivity level required or by the percentage of each motorized aperture forecast.

There is the possibility of connecting up to two motorized. For each one there is an output to open and another to close. The nominal time of opening of the motorized valves has to be superior to 20 seconds.

There is an alarm output.

The power supply to the unit is 24 Vac. Option 12 Vdc.

There are three inputs for starting the programs, and one input for detecting malfunctions. There is also one input for the conductivity sensor, with the transmitter integrated in the unit circuitry.

Sensor calibration is carried out from the keyboard.

It is easy to operate and program by means of three keys and a liquid crystal display with 13 mm characters.

Alarm for EC the highest and lowest values and the delay in the detection of the irregularity can be configured.

Configurable lag for the detection of the start up and malfunction inputs.

You can also stop or not the program in course when an alarm occurs.

The motorized valves can also be started up by hand.

Configuration of the motorized that will control the water with higher conductivity, as well as the one which will control the amount of water we want to save.

Possibility of programming a minimum aperture of the motorized.

The unit is housed in a waterproof polycarbonate box.

## **WARRANTY**

Agrónic 54 is compliant with all the norms defined by the CE.

The products created by Progrés enjoy a 2 year warranty against all manufacturing defects.

**SISTEMES ELECTRONICS**  
**PROGRES, S.A.**

Avda. Urgell, 23 - 25250 BELLPUIG (Lleida) España

Tel. (+34) 973 32 04 29 - Fax (+34) 973 33 72 97

info@progres.es      www.progres.es